



[Home](#) > [CC-Link Partner Product CC-Link](#) > [CC-Link Slave Digital I/O](#) > [BNI CCL-104-100-Z001](#)

CC-Link | Slave | Digital I/O

## Balluff Co.,Ltd.

BNI CCL-104-100-Z001

**Digital Input Modul, with 8 M12 Ports and 16 Digital Inputs. Distributed I/O box, Waterproof, Field mountable, IP67**



## Features

- 16 Digital Inputs
- IP 67 Water and Oil proof
- 8 Ports M12
- Field mountable
- Integrated Display for Address setting
- Integrated Display for diagnosis

## Specifications

Station type	Remote device station
Number of stations occupied	1 station
CC-Link version	Ver.1.10
External dimensions	68x224x36,9 mm
Mass	0.58 kg

## Contact us

<URL> <http://www.balluff.com/>

[← Back](#)

[top](#)

Contact/CC-Link Partner Association E-mail: [info@cc-link.org](mailto:info@cc-link.org)  
All Rights Reserved , Copyright CC-Link Partner Association.



[Home](#) > [CC-Link Partner Product CC-Link](#) > [CC-Link Slave Digital I/O](#) > [BNI CCL-202-100-Z001](#)

CC-Link | Slave | Digital I/O

## Balluff Co.,Ltd.

BNI CCL-202-100-Z001

**Digital Input Modul, with 8 M12 Ports and 8 Digital Outputs. Distributed I/O box, Waterproof, Field mountable, IP67**



## Features

- 8 Digital Outputs
- IP 67 Water and Oil proof
- 8 Ports M12
- Field mountable
- Integrated Display for Address setting
- Integrated Display for diagnosis

## Specifications

Station type	Remote device station
Number of stations occupied	1 station
CC-Link version	Ver.1.10
External dimensions	68x224x36,9 mm
Mass	0.58 kg

## Contact us

<URL> <http://www.balluff.com/>

[← Back](#)

[top](#)

Contact/CC-Link Partner Association E-mail: [info@cc-link.org](mailto:info@cc-link.org)  
 All Rights Reserved , Copyright CC-Link Partner Association.



[Home](#) > [CC-Link Partner Product CC-Link](#) > [CC-Link Slave Digital I/O](#) > [BNI CCL-302-100-Z001](#)

CC-Link | Slave | Digital I/O

## Balluff Co.,Ltd.

BNI CCL-302-100-Z001

**Digital Input Modul, with 8 M12 Ports and max. 16 Digital Inputs / Outputs, free configurable. Distributed I/O box, Waterproof, Field mountable, IP67**



## Features

max. 16 Digital Outputs / max. 16 Digital Inputs free configurable in total 16

IP 67 Water and Oil proof

8 Ports M12

Field mountable

Integrated Display for Address setting

Integrated Display for diagnosis

## Specifications

Station type	Remote device station
Number of stations occupied	1 station
CC-Link version	Ver.1.10
External dimensions	68x224x36,9 mm
Mass	0.58 kg

## Contact us

<URL> <http://www.balluff.com/>

[← Back](#)

[top](#)

Contact/CC-Link Partner Association E-mail: [info@cc-link.org](mailto:info@cc-link.org)

All Rights Reserved , Copyright CC-Link Partner Association.



[Home](#) > [CC-Link Partner Product CC-Link](#) > [CC-Link Slave Digital I/O](#) > [BNI CCL-305-100-Z001](#)

CC-Link | Slave | Digital I/O

## Balluff Co.,Ltd.

BNI CCL-305-100-Z001

**Digital Input Modul, with 8 M12 Ports and 8 Digital Inputs / 8 Digital Outputs. Distributed /I/O box, Waterproof, Field mountable, IP67**



## Features

- 8 Digital Outputs / 8 Digital Inputs
- IP 67 Water and Oil proof
- 8 Ports M12
- Field mountable
- Integrated Display for Address setting
- Integrated Display for diagnosis

## Specifications

Station type	Remote device station
Number of stations occupied	1 station
CC-Link version	Ver.1.10
External dimensions	68x224x36,9 mm
Mass	0.58 kg

## Contact us

<URL> <http://www.balluff.com/>

[← Back](#)

[top](#)

Contact/CC-Link Partner Association E-mail: [info@cc-link.org](mailto:info@cc-link.org)  
All Rights Reserved , Copyright CC-Link Partner Association.